

ECOflO COMPACT



			Model	
			20/190	20/190L
Product code			7681595	7681596
Energy	Heat input (gross)	kW	21.1	21.1
	Heat output (gross)	kW	19	19
	Gross thermal efficiency	%	91%	91%
ErP	NO _x emissions (0% O ₂)	mg/kWh	27.6	22.9
	NO _x emissions (0% O ₂)	ppm	15.7	13
	ErP efficiency rating		A	A
	Noise level	dB(A)	49.3	49.3
Gas data	Gas flow rate (natural gas)	m ³ /hr	1.5	-
	Gas flow rate (propane)	kg/h	-	0.99
Water	Storage capacity	litre	189	189
	Recovery rate through 50°C Δt	litre/hr	350	350
	Recovery rate through 56°C Δt	litre/hr	297	297
	Operating pressure (unvented)	bar	3.5	3.5
	Minimum working pressure at 10.3bar	bar	1	1
	Maximum working pressure	bar	10.3	10.3
Electrical	Fuse rating	amp	5	5
	Electrical power consumption	W	300	300
	Electrical requirements	V	230	230
Misc	Weight full	kg	305	305
	Weight empty	kg	124	124
	Maximum outlet temperature	°C	80	80
Connection sizes	Inlet/outlet connections	BSP	¾	¾
	Return connection	BSP	¾	¾
	Gas connection	BSP	½	½
	Height of tank	mm	1429	1429
	Water heater height	mm	1710	1710
	Diameter	mm	610	610
Service clearance	Front	mm	600	600
	Sides	mm	300	300
	Above	mm	450	450
Shipping	Shipping width	mm	778	778
	Shipping depth	mm	699	699
	Shipping height	mm	1890	1890
	Shipping weight	kg	135	135
Accessories	Horizontal flue kit		7697176	7697176
	Vertical flue kit		7697174	7697174
	1 metre length flue		7697185	7697185
	1m cuttable flue extension		7697186	7697186
	0.5 metre flue		7697184	7697184
	90° bend		7697182	7697182
	45° bend		7697183	7697183
	Wall terminal guard		7697179	7697179
	Horizontal terminal		7697181	7697181
	Weather slate angled 25° - 45°		7697177	7697177
	Weather slate flat		7697178	7697178
	Air cover for wall & roof terminal		7697187	7697187
	Unvented system kit		7703928	7703928
	Correx powered anode kit		7705307	7705307
Remote enable kit		7697190	7697190	



Sales 0345 070 1055

Technical 0345 070 1057

Web andrewswaterheaters.co.uk

[linkedin.com/company/andrews-water-heaters](https://www.linkedin.com/company/andrews-water-heaters)

@AndrewsWH