VAL2 HNK C CD

VALUE Tap Range Lever High Neck Pillar Taps Chrome With Ceramic Disc Valves



Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability

Product Certifications:

WRAS Certificate No: 1905900 WRAS Expiry Date: 31/05/2024

APPROVED PRODUCT

• Supplied with 3" (76mm) metal lever handles

| Specification | | | | |
|-----------------------------------|------------------------------------|--|--|--|
| Product Type: | Kitchen Taps | | | |
| Main Construction Material: | Brass | | | |
| Mount Type: | Deck Mounted | | | |
| Handle Type: | Lever Handles | | | |
| Connection Inlet: | 1/2" BSP | | | |
| Connection Outlet: | Flow Straightener | | | |
| Number of Tap Holes: | 2 | | | |
| Valve/Cartridge Type: | 1/2" Ceramic Disc Valve - 1/4 Turn | | | |
| Plumbing System Requirements: | Suitable for all plumbing systems | | | |
| Minimum Dynamic Pressure: | 0.2 bar | | | |
| Maximum Dynamic Pressure: | 5.0 bar | | | |
| Maximum Hot Water Temperature: °C | 65 | | | |
| Maximum Static Pressure: (bar) | 10 bar | | | |
| Flow Type: | Single Flow | | | |
| Isolation Included: | No | | | |
| Check Valve Supplied: | No | | | |
| | | | | |

Dimensions (measurements in mm)



BRISTA

D3

| | Flow | Flow Rates (I/min) | | | | | | | |
|--|-----------------------|--------------------|------|------|------|------|------|--|--|
| | System Pressure (bar) | 0.2 | 0.5 | 1 | 2 | 3 | 5 | | |
| | Hot | 7.9 | 13.1 | 18.7 | 27.1 | 33.0 | 42.9 | | |
| | Cold | 7.6 | 13.0 | 18.7 | 27.2 | 33.1 | 42.5 | | |
| | | | | | | | | | |



66.11/min

For more products, visit our website:

http://www.bristan.com

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.