



0151454000  
PAC EX100 Silent



0151401001  
PAC ANK92 Silent



0151401000  
PAC AN112 Silent



0151800039  
PAC N87 Silent



0151801034  
PAC AN97 Real Feel



0151800025  
PAC N81



Model	PAC EX100 Silent	PAC AN112 Silent	PAC AN97 Real Feel	PAC ANK92 Silent	PAC N87 Silent	PAC N81
Cat No.	0151454000	0151401000	0151801034	0151401001	0151800039	0151800025
Rated Voltage/Frequency (V~Hz)	220/240-50	220/240-50	220/240-50	220/240-50	220/240-50	220/240-50
Maximum cooling capacity in air to air mode <sup>(1)</sup>	10000	11000	10700	10000	9800	9400
Cooling capacity <sup>(2)</sup>	2.5	2.9	2.7	2.5	2.5	2.4
Input power <sup>(2)</sup>	700	950	1000	800	940	900
EER <sup>(2)</sup>	3.6	3.1	2.6	3.1	2.6	2.6
Energy Efficiency Class	A++	A+	A	A+	A	A
Hourly Energy Consumption (kWh/1h) <sup>(2)</sup>	0.7	0.9	1.0	0.8	0.9	0.9
Airflow (min/med/max fan speed) (m <sup>3</sup> /h)	250/310/350	250/310/350	250/310/350	250/310/350	250/310/350	250/310/350
Max dehumidifying quotient (in dehum. mode) (Ltr/24h) <sup>(3)</sup>	32	41	36	32	34	32
Dehumidifying quotient (cooling mode) (Ltr/24h) <sup>(4)</sup>	20	26	23	20	21	20
Pressure noise level (min-max) dB(A) <sup>(5)</sup>	49-53	47-50	50-52	47-50	50-52	50-52
Maximum Sound Power Level dB(A)	64	63	63	62	63	63
Standby power consumption (W)	<1	<1	<1	<1	<1	<1
Refrigerant gas	R290*	R290*	R410A**	R290*	R410A**	R410A**
For rooms up to (m <sup>2</sup> )	110	110	95	85	85	80
Display	LED - with CLI	LED - with CLI	LED - with CLI	LED	LED	LED
Room thermostat	•	•	•	•	•	•
Setting temperature	°C	°C	°C	°C	°C	°C
Only fan function	•	•	•	•	•	•
Fan speed	3	3	3	3	3	3
Silent operation	•	•	•	•	•	•
Dehumidifying function/Condensate recycling system	•/•	•/•	•/•	•/•	•/•	•/•
Timer (hr)	24	24	24	24	12	12
Auto-diagnosis/LCD IR remote control	•/•	•/•	•/•	•/•	•/•	•/•
Dimensions (HxWxDmm)	806x440x387	750x449x395	750x449x395	750x449x395	750x449x395	750x449x395
Weight (kg)	30	30	30	30	30	30