

DEMAND SIDE RESPONSIVE ELECTRIC RADIATORS



Demand Side Responsive Electric Heating

EHC's unique **DSR** Electric Combination Radiators have **In-Built Wi-Fi** capability that can be activated using the optional **DSR** Gateway. They are the first German Electric Radiators of their type that can be controlled via a bespoke APP Control System. This easy to install system is suitable as a complete central heating system or stand-alone Radiators. They can be individually controlled using the Digital Controller located on the side of the Radiator or alternatively using the bespoke APP.

- Control your heating anytime and anywhere
- Fully controllable for both Time and Temperature
- Energy saving Eco Control APP
- Limit electricity consumption to avoid exceeding maximum power available
- Monitor your electricity consumption
- Open window sensor saving energy and money
- Use individually or as a fully integrated central heating system





- Portable (on castors or feet) or fixed (wall-mounted)
- 500w-2400w output
- Patented heating tablets continue to radiate heat for up to 45 minutes offering increased comfort
- High fin design provides up to six times the surface area of a conventional radiator
- Maintenance free and 100% Energy Efficient

Simply connect to the Internet using a Smartphone, Tablet or PC and you will be able to open your EHC Smart APP to control your heating 24/7. Our APP is compatible with both Apple and Android products.

EHC Radiator Technology

Our unique Combination Radiators are designed to store the heat directly into the Magmatic Heat Retention Tablets without any loss of energy.

When the EHC Radiators have achieved their required temperature the Electronic Thermostat will cut the power to the Radiator. The Radiator will continue to provide heat, which has been stored in the Magmatic tablets, for up to 45 minutes with no Outside -High Fin Surface area

Installation kit

for wall fastening

further use of electricity. The Radiators will use approximately 20 – 30 minutes of electricity per hour, depending on the building fabric and the outside temperature.

The contacts inside the Radiators are protected with heat shrinkable insulated sleeves to ensure optimum safety. Multiple thermocouples within each Radiator provideoverheat protection for additional safety.

Inside - Magmatic heat retention tablets

DSR Time & Temperature

Our energy saving Open Window feature which does not require contacts on the window can be enabled or disabled using the Engineer Settings on each Radiator. When using this feature the **Radiator constantly monitors** the room temperature. If the Radiator detects a 2.4° drop in temperature over a 4 minute period the Radiator will automatically switch off for 30 minutes. Thereafter the Radiator will return to its previous settings however it will continue to repeat the process when a 2.4° drop in temperature is detected.



Technical Specification

Stock Code	Output	Dimensions (mm) W x H x I	Weight D (kg)
EH500.38.63DSR	500watt	380 630 7	0 22
EH800.38.63DSR	800watt	380 630 7	0 22
EH1000.68.63DSR	1000watt	680 630 7	0 36
EH1200.68.63DSR	1200watt	680 630 7	0 36
EH1500.98.63DSR	1500watt	980 630 7	0 50
EH1800.98.63DSR	1800watt	980 630 7	0 50
EH2000.128.63DSR	2000watt	1280 630 7	0 62
EH2400.128.63DSR	2400watt	1280 630 7	0 62
EH500.68.34DSR	500watt	680 340 7	0 21
EH1000.85.34DSR	1000watt	850 340 7	0 24.5
EH1600.128.34DSR	1600watt	1280 340 7	0 34.5
EH2000.158.34DSR	2000watt	1580 340 7	0 38
EH1200.38.124DSR	1200watt	380 1240 7	0 35
EH1800.55.124DSR	1800watt	550 1240 7	0 58
EH2200.68.124DSR	2200watt	680 1240 7	0 62

DSR Smart Wi-Fi APPs

Home Page Menu

Displays the heating status, temperature and operational functions of your system. You can select how you want to program your Heaters 24/7 however you have the facility to make changes to your heating requirements anytime, anywhere.



Consumption Limiter Menu

All homes have a maximum electrical power capacity. In order to stay within the limits of the capacity the Smart system has an inbuilt electricity consumption monitor / limiter. Our Smart Kit has an optional 100amp Power Meter Clamp.






Power & Temperature Statistics Menu

The Smart system enables you to monitor the consumed power and temperatures at any time.



Individual Heater Devices Menu

The Smart Wi-Fi system allows you to add, delete and prioritise Heaters at any time to provide you with full system control.



- Smart Gateway
- Power Meter Clamp (optional)

EHC Radiator Accessories



Feet Stands, Castors and Radiator Feet Supports



Blantyre Industrial Estate, Blantyre G72 OUP Tel: 01698 820533 Fax: 01698 825697 Email: info@electric-heatingcompany.co.uk
www.electric-heatingcompany.co.uk



Disclaimer - All figures quoted are correct at the time of printing and may be subject to change