

RF-link Carbon Monoxide Alarm

MODEL		WARRANTY
CO10-RF	Sealed 10-year lithium battery	7 YEARS

- **RF-LINK** Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA)
- 10 year lithium powered
- Firehawk Data Scan – data extraction using Firehawk App
- Proven top quality electrochemical sensor
- Small and Compact
- Ease of linking and installation



DATA SCAN APP

Scan your compatible FireHawk CO alarm for device information



CE
UK
CA

BS EN 50291-1:2018
BS EN 50291-2:2019
KM 573122

TECHNICAL SPECIFICATION	
Power Supply	Sealed Lithium Battery
Alarm Type	Standalone Long Life
Alarm interlink (RF-Link)	Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA)
Operating frequency	868MHz
Indicators	Green = Power. Red = Alarm. Amber = Fault
Alarm Installation positions	Fix to ceiling or wall
Test/Hush	Test & Silence
Dimensions	30mm x 65mm x 100mm
Weight	80g
Alarm Sound level	85dB (A) at 3m
Use in:	Dwelling houses, Caravans/motorhomes & Leisure vehicles, Boats.
Operating Temperature	-10°C or greater +40°C
Operating Humidity	30% - 90% RH
IP Rating	IP42
Packaging	Individual box & Outer carton (Recyclable cardboard)
Master pack/Outer carton	10 units
Maximum interlinked alarms	20 x RF-LINK alarms (Maximum of 15 if used with FHN800HIA)
Barcode	EAN - 5055278500894
Approval/Certified to	BS EN50291-1:2018; BS EN50291-2:2019
Warranty	7 years