



Geberit Mapress Copper adaptor with female thread (gas)



Example image

APPLICATION PURPOSES

- For natural gases
- For liquefied gases
- For natural and liquefied gases

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Marked in yellow
- Seal ring made of HNBR, yellow

- Pressing socket with yellow protection plug

TECHNICAL DATA

Product material Gunmetal / lead-free gunmetal

Art. no.	DN	d, ø mm	Rp "	Product material	L cm	Z cm
34683	12 / 15	15	1/2	Lead-free gunmetal	3.8	0.5
34693	12 / 20	15	3/4	Lead-free gunmetal	3.9	0.4
34684	15	18	1/2	Lead-free gunmetal	3.7	0.4
34685	15 / 20	18	3/4	Lead-free gunmetal	3.9	0.4
34686	20 / 15	22	1/2	Lead-free gunmetal	3.6	0.2

<i>Art. no.</i>	<i>DN</i>	<i>d_e mm</i>	<i>Rp₁</i>	<i>Product material</i>	<i>L cm</i>	<i>Z cm</i>
34687	20	22	3/4	Lead-free gunmetal	3.9	0.3
34688	20 / 25	22	1	Lead-free gunmetal	4.3	0.5
34689	25	28	1	Lead-free gunmetal	4.5	0.5
34690	32	35	1 1/4	Lead-free gunmetal	5	0.5
34691	40	42	1 1/2	Lead-free gunmetal	5.4	0.5
34692	50	54	2	Lead-free gunmetal	6.3	0.5