

[Specification](#) [Fiche](#) [EU Label](#) [UK Label](#)

Product Specification



Product Code: TCEMVI-0250NFC

Item Description: 250L CYCLONE IND SHORT C

C




Capacity	Brand	ERP Type	Item Category Code	Product Group Code	Model
250 L	CYCLONE	IndirectUnvented	Stainless	CYCLONE	INDIRECT

Product Specification

Actual capacity (Ltr)	247	Thermal insulation	DENSE PU FOAM
Unit weight empty (kg)	49	Cylinder material	LDX 2101
Unit weight full (kg)	299	Outer casing	COATED MILD STEEL
No immersions	1	Coil material	316L STAINLESS STEEL
Immersion spec	3KW@230V	Foam thickness	0
Max mains water pressure (Bar)	10	Operating temp (C)	60
Operating pressure (Bar)	7	Safety valve temp (C)	90
Tested to standard	BS EN 12897:2016	Warranty terms (Year)	1Y
No heat exchangers	1	Heat loss	2.14
Coil 1 rating (kW)	26.55	Coil 1 surface area (m ²)	.77
Coil 1 max prim pressure (Bar)	3.5	Coil 1 resistance (Bar)	.06

Dimensions

A (mm)	13900
B (mm)	600
C (mm)	218
D (mm)	383
E (mm)	608
F (mm)	673
G (mm)	698
H (mm)	1133



Click or scan here to view the product page:



<https://jouleuk.co.uk/products/cyclone-indirect/>



Test Standard: BS EN 12897:2016

Joule UK
Unit 3, Leftfield Park, Park Road,
Pontefract, West Yorkshire,
WF8 4PS, UK

Joule Ireland
Unit 407 NW Business Park,
Cappagh Road, Ballycoolin,
Blanchardstown,
Dublin

