



PRODUCT

3SFW

Heat Alarm with wireless capability

DESCRIPTION



Mains-powered heat alarm from the 'Slick' range of fast-fit alarms that can be interconnected with up to 23 other Kidde and Firex mains alarms. Optional wireless capability using Wireless Alarm Base (RF-SFTP) for wire-free interconnection.

KEY FEATURES

- **Unique fast-fit system** with separate base plate, for ease of fitting and maintenance
- **Integral, double-decker screwless terminal block** for fast, push-fit connection
- **Auto reset** after activation with latching LED allowing the initiating alarm to be identified
- **Separate Test and Hush™ buttons** to test and temporarily silence nuisance alarms
- **Alkaline back-up battery** provides continuous operation in the event of mains failure
- **Interconnectable** with other Kidde mains smoke and heat alarms and Kidde mains CO alarms using 'Smart Interconnect' technology
- **Tamper-resistant locking device** – prevents unauthorised removal without the use of a tool
- **Wireless capability** – use with optional Wireless Alarm Base (RF-SFTP) for RF interlink function
- **Deep Base** – allows easier wiring

WHERE TO USE

This mains-powered unit can be used throughout the home in humid or dusty environments where an optical or ionisation smoke alarm is unsuitable, e.g. kitchens, loft spaces and garages. The 'Slick' range requires installation by a professionally qualified electrician and complies with UK Building Regulations for new housing and associated standards (Grade D, BS5839, Part 6).

GENERAL FEATURES

| | |
|-----------------------|--|
| Model | 3SFW |
| Power Supply | 230V mains |
| Temperature Range | 0°C to +40°C |
| Humidity Range | Up to 93% Relative Humidity (RH) non-condensing |
| Storage and Transport | -20°C to +60°C and 5–95% relative humidity (RH) non-condensing |
| Alarm Dimensions | 135 x 135 x 70mm (including 'Slick' mounting base) |
| Alarm Weight | 274g |
| Warranty | 6 years |
| Approvals | BSI certified to BS5446 Part 2:2003 CE tested and certified |
| Associated Standard | BS 5839 Part 6 Grade D |



BS5446 Part 2: 2003
Licence no: KM503753

PRODUCT

3SFW

Heat Alarm with wireless capability



POWER SOURCE

230V mains

SENSOR TYPE

Thermistor (thermal resistor)

TECHNICAL SPECIFICATION

Note: Specifications are subject to variation by improvement and change

| | |
|----------------------------|--|
| Sensor | Thermistor (Thermal resistor) within detection unit |
| Sensitivity | Complies with BS 5446 Part2:2003, as a Class A2 device, alarms between 54°C and 70°C |
| Button Test | Simulates the effect of heat at the sensor, checks electronics and sounder |
| Automatic Self-test | Circuitry is tested every 40 seconds and unit beeps if fault is detected |
| Supply Voltage | 230V AC, 50 Hz (nominal UK voltage) |
| Power Consumption | Maximum 80mA |
| Battery Back-up | User-replaceable alkaline 9V battery (MX1604) |
| Battery Monitoring | Battery is monitored and unit emits a single chirp every 40 seconds if a fault is present |
| Low Battery Warning | 30-day low battery indicator |
| Power-on Indicator | Continuous green LED |
| Alarm Sounder | Electronic piezo-electric sounder (T3 pattern sound - three pulses - space - three pulses) |
| Sound Output | 85dB (A) minimum at 3 metres |
| Alarm Frequency | 3.2 kHz typical |
| Alarm Status | Red LED flashes rapidly, typically once every 2/3 seconds = unit sensing a fire event Red LED double flashes every 30 seconds = unit is triggering unit (press test button to unlatch) Red LED flashes once every ten seconds = in hush condition (auto-reset after 7 minutes) Red LED flashes once every 35 seconds = normal quiescent operation |
| Interconnection | Up to 24 units (smoke, heat and CO) can be hardwire interconnected using SMART® interconnect system with optional control (see below) Up to 15 units can be wireless interconnected using appropriate Wireless Base RF-SFTP |
| Optional Controls | Wireless Base Remote Test and Hush Unit (KN-RTH-RF) when used with Wireless Base |
| Fixing | 'Slick' mounting deep base as supplied |
| Base Cable Connect. | Screwless Terminal Block with slot release feature for conductor |

PACKAGED SPECIFICATION

| | BOX |
|-----------------|--------------------------|
| Order Code | 3SFW |
| Pack Dimensions | 142 x 142 x 82mm |
| Pack Weight | 320g |
| UPC Barcode | 00-25417-199994 |
| Case Quantity | 6 |
| Case Dimensions | 160 x 295 x 258mm |
| Case Weight | 2.5kg |
| ITF Outer Code | n/a |

