

Mira Element EV

Mixer Shower



SUITABLE FOR ALL SYSTEMS



5 YEAR GUARANTEE

Its simple, uncluttered look is ideal for a contemporary or family bathroom, plus its single control makes it easy to use.

Product Information

Description	Colour	Product No.
Mira Element EV	Chrome	1.1910.001
Mira Element Exposed Valve only	Chrome	1.1910.002

Features & Benefits

Temperature control

Thermostatic temperature stability certified to TMV2

Easy to fit

Quickly and easily fits onto reversed inlet supplies

Adjustable slide bar fits over holes left by previous shower kit (400mm-600mm)

Easy to service

Easily replaceable pull out large, long-life filters

Patented 'easy clip' system makes the cartridge easy to replace

For your customer

Single control for flow and temperature

Space saving refined slim valve maximises showering space

Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure

Large 4 spray 11m showerhead with rub-clean nozzles



Product Specification

Tech Details

Temperature control

Control type: Thermostatic

Installation

Water entry points: Rising, falling or rear

Inlet connections: 15 mm compression (EV, BIV & BIR)

Outlet connections: ½" BSP Male Flat Face (EV) or 15mm compression (BIV & BIR)

Reversed inlets supported: Yes

Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)
55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (Rain+ spray at handset): 11.1 l/min at 0.5 bar,
Valve only: 17.3 l/min at 0.5 bar

Temperature stability: ± 2°C

Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp: Factory set to 41°C

Adjustable maximum temperature for on-site conditions

Approvals

WRAS approved (Water Regulations Advisory Scheme)

TMV2 certified



Dimensions

