



Model 66

Category Benefits

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Environmentally responsible, helping reduce the amount of waste that goes to landfill sites

Features

- 1-stage grind technology
- High-torque Dura-Drive[®] induction motor
- Built-in air switch in chrome and brushed steel
- 4 Year guarantee
- Stainless steel grind elements
- Continuous feed
- Overload protection
- Quick Lock[®] mounting assembly for faster, easier installation
- Cast lugs
- Removable sound baffle

Dimensions (mm)

	Model 66		
	А	318	۵
	В	168	E
	С	64	

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.

Sample Specification

ര

185 131 Food waste disposer(s) shall be InSinkErator[®] Model 66 with 1-stage grind technology, .75 hp motor, auto-reverse grind system, stainless steel grind elements and built-in air switch with chrome and brushed steel options.

Guarantee: 4 Year parts and service.

The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.

Specifications

Type of Feed	Continuous	Grind Chamber	980 ml	
On/Off Control	Built-In Air Switch	Capacity		
Motor	Single Phase	Motor Protection	Manual Reset Overload	
Time Rating	Intermittent	Average Water Usage	Approximately 4.0 L per Person per Day	
Lubrication	Permanently Lubricated Upper & Lower Bearings	Average Electrical Usage	3-4 KWH per Annum	
Shipping Weight	8.2 kg	Drain Connection	1-1/2" (3.81 cm)	
(Approx.)		Dishwasher Drain	Yes	
Overall Height	318 mm	Connection		
Grind Technology	1-Stage Grind Technology			
Volts/Hz	HP	RPM	RPM Average Load	
120V, 60 Hz	.75	1725	8.1 A	
220-240V, 50 Hz	.75	1425	1425 405 W	

1725

.75

InSinkErator Division Suite 6, Building 6 Hatters Lane Croxley Green Business Park Watford HERTS WD18 8YH United Kingdom

Sales Tel: (0) 1 923 297 880 Service Tel: (0) 800 389 3715 www.insinkerator.co.uk

InSinkErator Division Emerson Electric Co. 4700 21st Street Racine, WI 53406-5093 USA Sales/Service Tel: 262-554-3652 www.insinkerator.com/worldmap.html Download a QR Reader App to Smartphone

220-240V, 60 Hz



EMERSON

405 W

The Emerson logo is a trademark and a service mark of Emerson Electric Co. The mounting collar configuration is a trademark of Emerson Electric Co. InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models. © 2015 InSinkErator, InSinkErator® is a business unit of Emerson Electric Co. All Rights Reserved.

EX612-15F-64-37