RTO RF - RT1 RF - RT7 RF

Take control, the right temperature all the time, easy to install, easy to use





in France



warranty



Stylish and slim



Suitable for all heating applications







Energy class









Table stand



Easy to use



Wireles

In a few words ...

This digital room thermostat has been designed for easy operation and is intended to make your life easier and help you save energy and money. The extra large LCD and ambient temperature digits mean that the display can be read from across the room and the simple rotary dial makes it the perfect for everyone who wants a digital thermostat that is easy to understand.

RT1 RF - RT7 RF: The slide control operation and simple programming method means that everyone can set their own convenient schedule for each day of the week. Having the ability to customise each day of the week allows for greater efficiency savings.

This digital thermostat is just one of a range of products that can provide the right solution for controlling your heating system in an easy and efficient way, whether it is a new installation or an improvement to an existing one.



Operating modes easy to select

Features

RT0 RF: Digital room thermostat:

- Room temperature control.
- Two choices of installation: Wall-mounted or on a table stand.

RT1 RF: Daily programmable room thermostat:

- Room temperature control.
- Operating modes: Auto, Comfort, Eco, Heating on Standby with frost protection.
- Boost function for 1 hour: temporary Comfort temperature.
- Single day programming.
- 2 programmable comfort periods.
- Programme lock.
- Service interval function.
- Two choices of installation: Wall-mounted or on a table stand.



- White backlit display.
- Room temperature control.
- Operating modes: Auto, Comfort, Eco, Heating on Standby with frost protection.
- Boost function for 1 hour: temporary Comfort temperature.
- Single day or multiday programming.
- 3 programmable comfort periods.
- Programme lock.
- Service interval function.
- Two choices of installation: Wall-mounted or on a table stand.





| Technical specifications

- White plastic housing RAL 9016.
- l 2x AA (LR6) batteries supplied 2 years typical life.
- I Wall mounting plate and table stand supplied.

Type of control:

- 2 point switching (ON/OFF).
- TPI (Time Proportional & Integral) (RT1 RF / RT7 RF versions).
- Relay output on receiver: 5(2)A.
- Radio frequency: 2401.5MHz ~ 2477.5MHz.

| Environment:

- IP30.
- Operating temperature: 0°C to +40°C.
- Setpoint temperature: +5°C to +30°C.
- Storage temperature: from -10°C to +60°C.

- Humidity: 80% at +25°C (without condensation).
- Manufactured on ISO 9001 V2008 certified site.

I Standards:

- Transmitter:

R&TTE Safety	R&TTE - EMC	R&TTE - RF	RoHs
EN62311	EN301489-1 EN301489-3	EN300440-1 EN300440-2	EN50581
- Receiver:			
R&TTE Safety	R&TTE - EMC	R&TTE - RF	RoHs
EN60730-1 EN62479	EN301489-1 EN301489-3	EN300440-1 EN300440-2	EN50581

Models	References	Designations	Heights (mm)	Widths (mm)	Depths (mm)
RTO RF	RTEORFa	Wireless digital room thermostat	95	120	27
RT1 RF	RTE1RFa	Wireless daily programmable digital room thermostat	95	120	27
RT7 RF	RTE7RFa	Wireless 7 day programmable digital room thermostat	95	120	27
RT7 RF B	RTE7RFBa	Wireless 7 day programmable digital room thermostat - black version	95	120	27