

OFXE Oil-filled Radiator



Technical Details					
Controls	Manually adjustable rotary thermostat (5 to 30°C)				
Construction	Durable epoxy-polyester powder coated steel casing				
Element	Compact, finned, mineral-filled sheathed type				
Installation	Plug in and go, supplied with cast aluminium foot kit				
Safety	Dual cut-outs, auto and manual reset				
IP Rating	IP20				
Supply	1.3 metres 3 core cable with fitted UK plug 1/N/PE ~230-240 V, 50Hz, Class I, with earth wire				
Colour / Finish	Metal Chassis - Traffic white (RAL 9016) Control mouldings - Traffic white (RAL 9016)				

Approvals and Guarantee						
Approvals:	BEAB Approved. UKCA and CE Marked					
Guarantee:	2 Years					
Country of Origin:	United Kingdom					
Manufacturer:	Glen Dimplex Heating & Ventilation (Glen Dimplex UK Ltd)					

Product Description

OFXE oil-filled radiators are suitable for domestic and commercial premises, providing a balance of convected and radiant heat just like a conventional radiator, but with the added advantage of 'plug-in' portability.

Key Features

- Oil-filled for uniform heat distribution
- Epoxy-polyester powder coated steel casing
- Manually adjustable rotary mechanical thermostat for temperature control (5 to 30°C)
- Neon `Power On' indicator



Model / Item No. (EAN Code = 5011139 + item No.)		OFX075E	090683	OFX100E	069060	OFX150E	090706	OFX200E			
Output (kW)	0.75		1.00		1.50		2.00				
Width A (mm)	570		840		1105		1373				
Height B (mm)	683		683		683		683				
Depth with feet (mm)	220		220		220		220				
Weight (kg)	10.5		15		19.5		24				
Packaging Details											
Pack Width (mm)	710		980		1245		1515				
Pack Height (mm)	705		705		705		705				
Pack Depth (mm)	97		97		97		97				
Packed Weight (kg)	11.1		15.8		20.8		24.3				
Ti / Hi	14/2		12 / 2		14/1		14/1				
Pallet Quantity (2.4m high)		28		24		14		14			