

PLE Panel Heater

PLE Panel Convactor Heater with Electronic 7-Day Timer

The PLE panel heaters feature an electronic timer which offers a 7-day programme with 6 heating periods per day. The digital control panel has an easy-to-read display and four large control buttons with tactile feedback. Easy to operate and designed with an electronic lock to prevent tampering with controls. Features open window detection which recognises a sudden temperature drop when a window is opened and turns the heating off to save energy. Once the window is closed, the temperature change triggers the heating to resume its normal operation. These slimline heaters with concealed digital controls have strengthened grilles to increase durability and feature a snap-on bracket on their wall mounting system which allows easy installation and dismantling for cleaning and decorating.

Ideal for hotels, offices, bedrooms, kitchens, bathrooms and laundries.

- 0.5kW, 0.75kW, 1kW, 1.25kW, 1.5kW or 2kW rating
- 7-day timer with electronic thermostat
- 6 heating periods per day
- Very quiet operation
- Open window detection
- Copy day function
- Concealed digital controls
- 4 operating modes: Programme, Boost, Setback & Manual
- 15-minutes Boost feature
- Comfort heat setting between 15°C to 35°C
- Setback temperatures can be used for frost protection or maintaining a minimum room temperature between 4°C to 15°C
- Automatic safety cut-out
- Can set temperatures in degrees Celsius or Fahrenheit
- Maintains temperature within 0.7 degrees
- Easy-to-read display
- Easy operation
- 4 large control buttons with tactile feedback
- Electronic child lock
- Optional control panel locking kit (PLK1)
- Slimline and clean design
- Splash proof to IP24 for use in bathrooms and other damp areas
- Hinged wall mounting system for easy installation and decorating
- Fitted with 1m of supply cable
- Finished in white or stainless steel



Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight
PLE050	0.5	430	93	442	4.0
PLE075	0.75	430	93	442	4.0
PLE100	1	430	93	614	5.0
PLE125	1.25	430	93	720	6.0
PLE150	1.5	430	93	720	6.0
PLE200(SS)	2	430	93	852	6.5

Note: (SS) denotes Stainless Steel.