

SHZ 100 S (GB)

PRODUCT-NO.: 232786

Price conscious hot water provision

In wall mounted cylinders, the amount of standby power consumed greatly influences the operating costs over time. Thanks to its exceptional insulation, this wall mounted cylinder offers terrific DHW convenience at an affordable price.

Simple, yet effective

The clearly structured control element enables variable temperature selection, while the individual LEDs provide information on the amount of heat currently stored.



The main features

Variable temperature selection

Electronic heat content indicator via LEDs

Temperature limit possible

For supplying one or more draw-off points with DHW

Quick heat-up key for higher DHW demand

Easy to maintain due to protective anode with consumption indicator

Low energy losses thanks to high grade thermal insulation

Special enamel coating for a long service life

Variable temperature selection

Frost protection integrated in the DHW cylinder



| Type | SHZ 30 S (GB) | SHZ 50 S (GB) | SHZ 100 S (GB) |
|----------|---------------|---------------|----------------|
| Part no. | 232783 | 232784 | 232786 |

Technical data

| | | | |
|---|----------|----------|----------|
| Connected load ~ 230 V | 1-4 kW | 1-4 kW | 1-4 kW |
| Power supply | 1/N/PE | 1/N/PE | 1/N/PE |
| Rated voltage | 230 V | 230 V | 230 V |
| Frequency | 50 Hz | 50 Hz | 50 Hz |
| Load profile | S | M | L |
| Energy efficiency class | B | C | C |
| Standby energy consumption/ 24 h at 65 °C | 0.52 kWh | 0.60 kWh | 0.94 kWh |
| Nominal capacity | 30 l | 50 l | 100 l |
| Mixed water volume 40 °C | 50 l | 80 l | 133 l |
| Temperature setting range | 35-70 °C | 35-70 °C | 35-70 °C |
| Max. flow rate | 18 l/min | 18 l/min | 18 l/min |
| Colour | white | white | white |
| IP rating | IP 24 | IP 24 | IP 24 |
| Height | 846 mm | 816 mm | 1126 mm |
| Width | 410 mm | 510 mm | 510 mm |
| Depth | 420 mm | 510 mm | 510 mm |
| Weight | 22.90 kg | 27.60 kg | 39.50 kg |



Type SHZ 150 S (GB)

Part no. 232788

Technical data

Connected load ~ 230 V 1-4 kW

Power supply 1/N/PE

Rated voltage 230 V

Frequency 50 Hz

Load profile XL

Energy efficiency class C

Standby energy consumption/ 24 h at 65 °C 1.19 kWh

Nominal capacity 150 l

Mixed water volume 40 °C 229 l

Temperature setting range 35-70 °C

Max. flow rate 18 l/min

Colour white

IP rating IP 24

Height 1521 mm

Width 510 mm

Depth 510 mm

Weight 52.00 kg

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.