

ZV900

Automatic Switch Load Controller

Features & Benefits

- Eliminates glow and flicker issues in LED/CFL lamps when used with 2-wire automatic light switches (i.e. Timed, PIR, Photocell automatic switches)
- Under 1W power consumption
- Built-in surge suppression
- No additional cabling to the switch required
- Fits in the ceiling through a 50mm hole
- Specifically designed to operate with Timeguard ZV700, ZV700B, ZV210, ZV215, DS1, ZV810, ST210 and ST810 when used with LED or CFL lighting
- The ZV900 is suitable for other companies 2-wire electronic wall switch products
- IP20 weatherproof rating



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface (In-line)
Earth Class Rating	Class I
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Standby Consumption	<1W
Switch Rating	6A Resistive, 5A Inductive, 3W - 200W CFL, 76W Fluorescent, 200W LED

Data sheet

ZV900

Light / Automatic Light Switches

Cable Entry(s)	Side Entry
Dimensions	Height 28mm, Width 119mm, Depth 42mm

General

Height (mm)	28
Width (mm)	119
Depth (mm)	42
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483013434
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536909500

Line Diagrams

