

TOWELRADS PISA LADDER RANGE



High Heat Output achieved by using 25mm bars.

Versatile, can be used on central heating or dual fuel systems.

For the full and extensive range of towel rails, elements and accessories please visit our website at www.towelrads.com.

Curved options available in white and chrome variants.

Max Working Pressure: 10 bar

Max Working Temp: 110 degrees C



Manufacturers
Warranty



Available in Chrome,
White, Black & Anthracite



FEATURES AND BENEFITS

- Classic ladder towel radiator for stylish, contemporary bathrooms
- Wide range of heights, widths and finishes available to suit any space
- 25mm bars give much better heat output than standard towel radiators with 19mm and 22mm tubes
- Curved towel radiators also available in this range
- An even higher output can be achieved by opting for one of our popular modern painted finishes
- Horizontal models also available to fit neatly under windows
- Can be connected to central heating or used with a dual fuel element for versatility
- Plenty of towel warming space

PISA WHITE STRAIGHT

| Height | Length | Product Code | Pipe Centres | Output at ΔT_{50k} | |
|--------|--------|--------------|--------------|----------------------------|------|
| | | | | Watts | BTU |
| 800 | 400 | 160001 | 355 | 316 | 1078 |
| | 450 | 160002 | 405 | 349 | 1191 |
| | 500 | 160003 | 455 | 383 | 1307 |
| | 600 | 160004 | 555 | 451 | 1539 |
| 1200 | 400 | 160005 | 355 | 471 | 1607 |
| | 450 | 160006 | 405 | 522 | 1781 |
| | 500 | 160007 | 455 | 572 | 1952 |
| | 600 | 160008 | 555 | 673 | 2296 |
| 1500 | 400 | 160009 | 355 | 592 | 2020 |
| | 450 | 160010 | 405 | 655 | 2235 |
| | 500 | 160011 | 455 | 718 | 2450 |
| | 600 | 160012 | 555 | 845 | 2883 |
| 1800 | 400 | 160013 | 355 | 716 | 2443 |
| | 450 | 160014 | 405 | 792 | 2702 |
| | 500 | 160015 | 455 | 869 | 2965 |
| | 600 | 160016 | 555 | 1021 | 3484 |

PISA WHITE CURVED

| Height | Length | Product Code | Pipe Centres | Output at ΔT_{50k} | |
|--------|--------|--------------|--------------|----------------------------|-------|
| | | | | Watts | BTU |
| 800 | 400 | 160017 | 355 | 343 | 1,170 |
| | 450 | 160018 | 405 | 386 | 1,317 |
| | 500 | 160019 | 455 | 429 | 1,464 |
| | 600 | 160020 | 555 | 515 | 1,757 |
| 1200 | 400 | 160021 | 355 | 495 | 1,689 |
| | 450 | 160022 | 405 | 556 | 1,897 |
| | 500 | 160023 | 455 | 618 | 2,109 |
| | 600 | 160024 | 555 | 742 | 2,532 |
| 1500 | 400 | 160025 | 355 | 626 | 2,136 |
| | 450 | 160026 | 405 | 705 | 2,406 |
| | 500 | 160027 | 455 | 783 | 2,672 |
| | 600 | 160028 | 555 | 940 | 3,207 |
| 1800 | 400 | 160029 | 355 | 764 | 2,607 |
| | 450 | 160030 | 405 | 859 | 2,931 |
| | 500 | 160031 | 455 | 954 | 3,255 |
| | 600 | 160032 | 555 | 1,145 | 3,907 |

PISA BLACK STRAIGHT

| Height | Length | Product Code | Pipe Centres | Output at ΔT_{50k} | |
|--------|--------|--------------|--------------|----------------------------|------|
| | | | | Watts | BTU |
| 800 | 400 | 170001 | 355 | 316 | 1078 |
| | 500 | 170002 | 455 | 383 | 1307 |
| | 600 | 170003 | 555 | 451 | 1539 |
| 1200 | 400 | 170004 | 355 | 417 | 1607 |
| | 500 | 170005 | 455 | 572 | 1952 |
| | 600 | 170006 | 555 | 673 | 2296 |
| 1600 | 400 | 170007 | 355 | 633 | 2160 |
| | 500 | 170008 | 455 | 768 | 2620 |
| | 600 | 170009 | 555 | 903 | 3081 |

PISA ANTHRACITE STRAIGHT

| Height | Length | Product Code | Projection | Pipe Centres | Weight KG | Water Content L | Output at ΔT_{30k} | | Output at ΔT_{50k} | | DF Max Imm Rate | n EXPO-NENT |
|--------|--------|--------------|------------|--------------|-----------|-----------------|----------------------------|------|----------------------------|------|-----------------|-------------|
| | | | | | | | Watts | BTU | Watts | BTU | | |
| 800 | 400 | 150001 | 65-88mm | 355 | 6 | 3.95 | 163 | 555 | 316 | 1078 | 300 | 1.22 |
| | 500 | 150002 | 65-88mm | 455 | 71 | 4.67 | 197 | 673 | 383 | 1307 | 400 | 1.22 |
| | 600 | 150003 | 65-88mm | 555 | 79 | 5.39 | 232 | 793 | 451 | 1539 | 400 | 1.22 |
| 1200 | 400 | 150004 | 65-88mm | 355 | 9.3 | 5.59 | 243 | 828 | 417 | 1607 | 300 | 1.23 |
| | 500 | 150005 | 65-88mm | 455 | 9.95 | 6.56 | 295 | 1005 | 572 | 1952 | 400 | 1.23 |
| | 600 | 150006 | 65-88mm | 555 | 10.95 | 7.53 | 347 | 1182 | 673 | 2296 | 400 | 1.23 |
| 1600 | 400 | 150007 | 65-88mm | 355 | 11.65 | 7.63 | 326 | 1112 | 633 | 2160 | 400 | 1.23 |
| | 500 | 150008 | 65-88mm | 455 | 12.75 | 8.98 | 396 | 1349 | 768 | 2620 | 600 | 1.23 |
| | 600 | 150009 | 65-88mm | 555 | 14.8 | 10.34 | 465 | 1587 | 903 | 3081 | 600 | 1.23 |

PISA CHROME STRAIGHT

| Height | Length | Product Code | Pipe Centres | Output at ΔT_{50k} | |
|--------|--------|--------------|--------------|----------------------------|------|
| | | | | Watts | BTU |
| 600 | 400 | 140001 | 355 | 158 | 539 |
| | 450 | 140002 | 405 | 175 | 597 |
| | 500 | 140003 | 455 | 193 | 659 |
| | 600 | 140004 | 555 | 228 | 778 |
| 800 | 300 | 140005 | 255 | 161 | 549 |
| | 400 | 140006 | 355 | 207 | 706 |
| | 450 | 140007 | 405 | 230 | 785 |
| | 500 | 140008 | 455 | 253 | 863 |
| | 600 | 140009 | 555 | 298 | 1017 |
| | 750 | 140010 | 705 | 367 | 1252 |
| 1000 | 400 | 140011 | 355 | 257 | 877 |
| | 500 | 140012 | 455 | 313 | 1068 |
| | 600 | 140013 | 555 | 370 | 1262 |
| 1200 | 300 | 140014 | 255 | 240 | 819 |
| | 400 | 140015 | 355 | 308 | 1051 |
| | 450 | 140016 | 405 | 342 | 1167 |
| | 500 | 140017 | 455 | 375 | 1280 |
| | 600 | 140018 | 550 | 442 | 1508 |
| | 750 | 140019 | 705 | 543 | 1853 |
| 1400 | 400 | 140020 | 355 | 361 | 1232 |
| | 450 | 140021 | 405 | 400 | 1365 |
| | 500 | 140022 | 455 | 439 | 1498 |
| | 600 | 140023 | 555 | 517 | 1764 |
| | 750 | 140024 | 705 | 635 | 2167 |
| 1600 | 300 | 140025 | 255 | 326 | 1112 |
| | 400 | 140026 | 355 | 415 | 1416 |
| | 450 | 140027 | 405 | 460 | 1570 |
| | 500 | 140028 | 455 | 505 | 1723 |
| | 600 | 140029 | 555 | 594 | 2027 |
| 1800 | 300 | 140030 | 255 | 371 | 1266 |
| | 400 | 140031 | 355 | 472 | 1610 |
| | 450 | 140032 | 405 | 522 | 1781 |
| | 500 | 140033 | 455 | 572 | 1952 |
| | 600 | 140034 | 555 | 673 | 2296 |
| | 750 | 140035 | 705 | 824 | 2811 |

PISA CHROME CURVED

| Height | Length | Product Code | Pipe Centres | Output at ΔT_{50k} | |
|--------|--------|--------------|--------------|----------------------------|-------|
| | | | | Watts | BTU |
| 600 | 400 | 140036 | 355 | 182 | 621 |
| | 450 | 140037 | 405 | 205 | 699 |
| | 500 | 140038 | 455 | 228 | 778 |
| | 600 | 140039 | 555 | 273 | 931 |
| 800 | 400 | 140040 | 355 | 274 | 935 |
| | 450 | 140041 | 405 | 308 | 1,051 |
| | 500 | 140042 | 455 | 342 | 1,167 |
| | 600 | 140043 | 555 | 411 | 1,402 |
| 1000 | 400 | 140044 | 355 | 321 | 1,095 |
| | 500 | 140045 | 455 | 400 | 1,365 |
| | 600 | 140046 | 555 | 481 | 1,641 |
| 1200 | 400 | 140047 | 355 | 352 | 1,201 |
| | 450 | 140048 | 405 | 396 | 1,351 |
| | 500 | 140049 | 455 | 440 | 1,501 |
| | 600 | 140050 | 550 | 528 | 1,802 |
| 1400 | 400 | 140051 | 355 | 426 | 1,454 |
| | 450 | 140052 | 405 | 479 | 1,634 |
| | 500 | 140053 | 455 | 532 | 1,815 |
| | 600 | 140054 | 555 | 639 | 2,180 |
| 1600 | 400 | 140055 | 355 | 504 | 1,720 |
| | 450 | 140056 | 405 | 569 | 1,941 |
| | 500 | 140057 | 455 | 632 | 2,156 |
| | 600 | 140058 | 555 | 760 | 2,593 |
| 1800 | 400 | 140059 | 355 | 548 | 1,870 |
| | 450 | 140060 | 405 | 617 | 2,105 |
| | 500 | 140061 | 455 | 686 | 2,341 |
| | 600 | 140062 | 555 | 823 | 2,808 |

TECHNICAL DIAGRAMS

PISA LADDER COLLECTION

