SPEC SHEET - AP430S

Zip Aquapoint

Aquapoint 4 is a sustainable, durable and efficient wallmounted hot water solution, suitable for both workplace and home environments. With four capacity options, the model boasts a number of innovative features, including its SmartEco mode and anti-legionella function.





MODEL	ENERGY EFFICIENCY	*DIMENSIONS	NOMINAL POWER	RE-HEAT TIME	CAPACITY
	CLASS (ERP)	W X D X H	RATING KW	(HH:MM)	(LITRES)
AP430S	В	420mm x 445mm x 510mm	2 kW @ 230V AC	00:59	31

Features and benefits

Glass lined steel inner container

Tested to 13 bar

Sacrificial anode

For protection against corrosion

Approvals

WRAS approval and CE endorsed

Insulation

High performance foam

External temperature control

Can be replaced without draining



Product detail

Specification type

Product code	AP430S	
Product name	Aquapoint 4 Unvented 30 Litre Overbasin SmartEco	
Energy Efficiency Class	В	
WRAS Approval	Yes	
Wras Number	1905042	

Capacity, weights & dimensions

Capacity (Litres)	31 L
Unit dimensions (W x D x H) mm	420 x 445 x 510
Empty weight	19kg
Filled weight	49kg


Electrical

2 kW @ 230V AC
230V
8.7 amps
24
Yes
1/2"BSP
lbar
-


The minimum water pressure will vary if a limescale filter is installed. Please contact us to discuss your requirements.

Typical Installation

All dimensions in mm



Discharge pipe arrangement



REF	DESCRIPTION		
1	Cold main		
2	Balanced cold connection		
3	Expansion vessel with wall bracket, from 'cold inlet set' take of		
4	Hot water outlet		
5	Temperature control		
6	Neon indicator		
7	Tundish to drain		
8	Temperature and pressure relief valve		
9	Expansion relief valve to drain via tundish		
10	Check valve		
11	Pressure reducing valve		
12	Isolating valve (not supplied)		
13	Drain valves (not supplied)		

